

MALE END VIEW

A = N/C
C = ORANGE
E = BLACK
G = GREEN
J = GREY
L = N/C
M = BROWN
N = TAN
O = VIOLET
P = RED
R = WHITE
S = YELLOW
T = PINK
U = BLUE

FEMALE END VIEW

A = N/C
C = ORANGE
E = BLACK
G = GREEN
J = GREY
L = N/C
M = BROWN
N = TAN
O = VIOLET
P = RED
R = WHITE
S = YELLOW
T = PINK
U = BLUE

SPECIFICATIONS

CONTACT CARRIER MATERIAL	NYLON
CONTACT MATERIAL/PLATING	COPPER ALLOY/GOLD
HOUSING MATERIAL	NYLON
COUPLING NUT MATERIAL/PLATING	BRASS/NICKEL
RATED CURRENT [A]	3.0 A
RATED VOLTAGE [V]	60 V AC/DC
OUTER JACKET MATERIAL/COLOR	PVC/BLACK
CONDUCTOR INSULATION MATERIAL	PVC
NUMBER OF CONDUCTORS [AWG]	12x24 AWG
DRAIN/SHIELD	26 AWG/ALUM.-POLYESTER FOIL
TEMPERATURE RANGE	-40°C TO +85°C (-40°F TO +185°F)
PROTECTION CLASS	MEETS IEC IP67

68.5 [2.69]

66.0 [2.60]

19.0 [0.75]

6.7 [0.26]

M16x1

METERS
SEE NOTE 1

CABLE LENGTH	TOLERANCE*
ALL LENGTHS	+ 4% (OR 50mm) OF LENGTH - 0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER
STRIP LENGTH	TOLERANCE*
0-7mm	±0.5mm
8-29mm	±1.0mm
30-49mm	±2.0mm
50-69mm	±3.0mm
70-100mm	±4.0mm
OVER 100mm	±5.0mm

*UNLESS OTHERWISE SPECIFIED

NOTES:

1. "*" INDICATES CABLE LENGHT IN METERS. CONTACT TURCK TO ORDER SPECIFIC LENGTHS.

RELATED DOCUMENTS

1.
2.
3.
4.

MATERIAL

SEE SPECIFICATIONS

FINISH

SEE SPECIFICATIONS

3RD ANGLE PROJECTION

THIS DRAWING IS CONFIDENTIAL AND THE PROPERTY OF TURCK INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED.

DRFT JBJ

DATE 08/11/00

APVD

SCALE 1=1.0

UNIT OF MEASUREMENT

MILLIMETERS

DO NOT SCALE THIS DRAWING

DESCRIPTION

RBS RBK 1614-755-*

IDENTIFICATION NO.

REV

F

3000 CAMPUS DRIVE
MINNEAPOLIS, MN 55441
1-800-544-7769
(763) 553-7300
(763) 553-0708 fax
www.turck.us

FILE: 777000772

SHEET 1 OF 1

F	UPDATE CABLE DIAMETER	KMY	03/08/12	37169
REV	DESCRIPTION	BY	DATE	ECO. NO.