

## SD 960 CY

Shielded continuous flex data cable for small bending radius



Marking for SD 960 CY 7852425:

SAB BRÖCKSKES · D-VIERSEN · 7852502 25 x 0.25 mm² SD 960 CY 24 AWG/25c 7852425 AWM Style 21083 80°C 300V CE

### Construction:

<b>Conductor:</b>	bare copper strands, extra fine wires
<b>Insulation:</b>	PVC, Tl2 acc. to EN 50363-3 + VDE 0207-363-3
<b>Color code:</b>	acc. to color code US 2, see page O/27
<b>Stranding:</b>	specially adjusted layering with non-woven tape over each layer
<b>Wrapping:</b>	non-woven tape
<b>Shielding:</b>	tinned copper braiding
<b>Wrapping:</b>	non-woven tape
<b>Jacket material:</b>	PVC, TM2 acc. to EN 50363-3 + VDE 0207-363-3
<b>Jacket color:</b>	black (RAL 9005)

### Outstanding features:

- good EMC characteristics
- very good flexibility
- small bending radius
- UV resistant jacket

### Technical data:

<b>Peak operating voltage:</b>	max. 350 V
<b>Voltage UL:</b>	300 V
<b>Testing voltage:</b>	conductor/conductor: 1500 V conductor/shielding: 1200 V
<b>Min. bending radius:</b> <i>continuously flexing:</i>	7.5 x O.D.
<b>Radiation resistance:</b>	8 x 10 <sup>7</sup> cJ/kg
<b>Temperature range:</b> <i>static:</i> <i>flexing:</i>	<b>DIN VDE</b> <b>UL/CSA:</b> up to +80°C -30/+70°C +5/+70°C
<b>Burning characteristics:</b>	flame retardant and self-extinguishing acc. to IEC 60332-1-2 + VDE 0482-332-1-2, UL VW-1
<b>Oil resistance:</b>	acc. to our internal standard, see page O/29
<b>Approvals:</b>	UR AWM, CE, EAC, RoHS
<b>Absence of harmful substances:</b>	acc. to RoHS directive of the European Union see page O/30

item no.	no. of conductors incl. ground	nominal outer-ø inch    mm	cable weight ≈lbs/mft
► 26 AWG (≈ 18/38) • 0.14 mm²			
7852602	2	0.177    4.5	17
7852603	3	0.185    4.7	20
7852604	4	0.205    5.2	24
7852605	5	0.220    5.6	28
7852607	7	0.252    6.4	38
7852610	10	0.295    7.5	45
7852614	14	0.335    8.5	60
7852618	18	0.366    9.3	73
7852625	25	0.433    11.0	100

item no.	no. of conductors incl. ground	nominal outer-ø inch    mm	cable weight ≈lbs/mft
► 24 AWG (≈ 32/38) • 0.25 mm²			
7852402	2	0.193    4.9	20
7852403	3	0.205    5.2	24
7852404	4	0.217    5.5	28
7852405	5	0.244    6.2	36
7852407	7	0.280    7.1	43
7852410	10	0.335    8.5	60
7852414	14	0.362    9.2	75
7852418	18	0.398    10.1	92
7852425	25	0.492    12.5	134

item no.	no. of conductors incl. ground	nominal outer-ø inch    mm	cable weight ≈lbs/mft
► 22 AWG (≈ 42/38) • 0.34 mm²			
7852202	2	0.201    5.1	22
7852203	3	0.213    5.4	26
7852204	4	0.228    5.8	31
7852205	5	0.252    6.4	40
7852207	7	0.291    7.4	49
7852210	10	0.346    8.8	69
7852214	14	0.378    9.6	86
7852218	18	0.425    10.8	114
7852225	25	0.512    13.0	153

Other dimensions and colors are available on request



#### Possible on request:

- 20 AWG & 19 AWG
- with gray jacket and colored conductors with reference to DIN 47100