



Product designation	Power contactor		
Product type designation	BG06		
<b>Contact characteristics</b>			
Number of poles	Nr.	3	
Rated insulation voltage $U_i$ IEC/EN	V	690	
Rated impulse withstand voltage $U_{imp}$	kV	6	
Operational frequency	min	Hz	25
	max	Hz	400
IEC Conventional free air thermal current $I_{th}$	A	16	
Operational current $I_e$			
	AC-1 ( $\leq 40^\circ C$ )	A	16
	AC-3 ( $\leq 440V \leq 55^\circ C$ )	A	6
	AC-4 (400V)	A	3.3
Rated operational power AC-3 ( $T \leq 55^\circ C$ )	230V	kW	1.5
	400V	kW	2.2
	415V	kW	2.4
	440V	kW	2.5
	500V	kW	3
	690V	kW	3
Rated operational power AC-1 ( $T \leq 40^\circ C$ )	230V	kW	6
	400V	kW	10
	500V	kW	13
	690V	kW	18
IEC max current $I_e$ in DC1 with $L/R \leq 1ms$ with 1 poles in series	$\leq 24V$	A	9
	48V	A	8
	75V	A	4
	110V	A	3
	220V	A	—
IEC max current $I_e$ in DC1 with $L/R \leq 1ms$ with 2 poles in series	$\leq 24V$	A	12
	48V	A	11
	75V	A	7
	110V	A	6
	220V	A	—
IEC max current $I_e$ in DC1 with $L/R \leq 1ms$ with 3 poles in series	$\leq 24V$	A	14
	48V	A	14
	75V	A	8
	110V	A	8
	220V	A	1
IEC max current $I_e$ in DC1 with $L/R \leq 1ms$ with 4 poles in series			

	≤24V	A	—
	48V	A	—
	75V	A	—
	110V	A	—
	220V	A	—
IEC max current Ie in DC3-DC5 with L/R ≤ 15ms with 1 poles in series	≤24V	A	6
	48V	A	5
	75V	A	2
	110V	A	1
	220V	A	—
IEC max current Ie in DC3-DC5 with L/R ≤ 15ms with 2 poles in series	≤24V	A	7
	48V	A	7
	75V	A	4
	110V	A	3
	220V	A	—
IEC max current Ie in DC3-DC5 with L/R ≤ 15ms with 3 poles in series	≤24V	A	9
	48V	A	9
	75V	A	5
	110V	A	4
	220V	A	0,5
IEC max current Ie in DC3-DC5 with L/R ≤ 15ms with 4 poles in series	≤24V	A	—
	48V	A	—
	75V	A	—
	110V	A	—
	220V	A	—
Short-time allowable current for 10s (IEC/EN60947-1)		A	96
Protection fuse			
	gG (IEC)	A	16
	aM (IEC)	A	6
Making capacity (RMS value)		A	92
Breaking capacity at voltage			
	440V	A	72
	500V	A	72
	690V	A	72
Resistance per pole (average value)		mΩ	10
Power dissipation per pole (average value)			
	I <sub>th</sub>	W	2.6
	AC-3	W	0.36
Tightening torque for terminals			
	min	Nm	0.8
	max	Nm	1
	min	Ibin	9
	max	Ibin	9
Tightening torque for coil terminal			
	min	Nm	0.8
	max	Nm	1
	min	Ibin	9
	max	Ibin	9
Max number of wires simultaneously connectable		Nr.	2

## Conductor section

AWG/Kcmil	max	12
Flexible w/o lug conductor section	min	mm <sup>2</sup> 0.75
	max	mm <sup>2</sup> 2.5
Flexible c/w lug conductor section	min	mm <sup>2</sup> 1.5
	max	mm <sup>2</sup> 2.5
Flexible with insulated spade lug conductor section	min	mm <sup>2</sup> 1.5
	max	mm <sup>2</sup> 2.5

Power terminal protection according to IEC/EN 60529

 IP20 when  
properly wired

## Mechanical features

## Operating position

	normal allowable	Vertical plan ±30°
--	---------------------	-----------------------

## Fixing

	Screw / DIN rail 35mm
--	--------------------------

## Weight

	g	185
--	---	-----

## Auxiliary contact characteristics

Thermal current I <sub>th</sub>	A	10
---------------------------------	---	----

## IEC/EN 60947-5-1 designation

	A600 - Q600
--	-------------

## Operating current AC15

230V	A	3
400V	A	1.9
500V	A	1.4

## Operating current DC12

110V	A	2.9
------	---	-----

## Operating current DC13

24V	A	2.9
48V	A	1.4
60V	A	1.2
110V	A	0.6
125V	A	0.55
220V	A	0.3
600V	A	0.1

## Operations

Mechanical life	cycles	20000000
-----------------	--------	----------

Electrical life	cycles	500000
-----------------	--------	--------

## Safety related data

Performance level B10d according to EN/ISO 13489-1	cycles	500000
	mechanical load	cycles 20000000

Mirror contacts according to IEC/EN 609474-4-1	Yes
--	-----

EMC compatibility	yes
-------------------	-----

AC coil operating	
-------------------	--

Rated AC voltage at 60Hz	V	460
--------------------------	---	-----

AC operating voltage	
----------------------	--

of 60Hz coil powered at 60Hz	
pick-up	
	min %Us 75

		max	%Us	115
	drop-out	min	%Us	20
		max	%Us	55
AC average coil consumption at 20°C				
of 50/60Hz coil powered at 50Hz				
		in-rush	VA	30
		holding	VA	4
of 50/60Hz coil powered at 60Hz				
		in-rush	VA	25
		holding	VA	3
of 60Hz coil powered at 60Hz				
		in-rush	VA	30
		holding	VA	4
Dissipation at holding ≤20°C 50Hz				
Max cycles frequency				
Mechanical operation				
Operating times				
Average time for Us control				
in AC				
Closing NO				
		min	ms	12
		max	ms	21
Opening NO				
		min	ms	9
		max	ms	18
Closing NC				
		min	ms	17
		max	ms	26
Opening NC				
		min	ms	7
		max	ms	17
in DC				
Closing NO				
		min	ms	18
		max	ms	25
Opening NO				
		min	ms	2
		max	ms	3
Closing NC				
		min	ms	3
		max	ms	5
Opening NC				
		min	ms	11
		max	ms	17
UL technical data				
Rated operational voltage AC (UL)				
Full-load current (FLA) for three-phase AC motor				
		at 480V	A	4.8
		at 600V	A	3.9
Yielded mechanical performance				
for single-phase AC motor				
		110/120V	HP	0.3
		230V	HP	1

for three-phase AC motor

200/208V	HP	1.5
220/230V	HP	2
460/480V	HP	3
575/600V	HP	3

**General USE**

Contactor

AC current A 16

Short-circuit protection fuse, 600V

High fault

Short circuit current	kA	100
Fuse rating	A	30
Fuse class		J

Standard fault

Short circuit current	kA	5
Fuse rating	A	30

Contact rating of auxiliary contacts according to UL

A600 - Q600

**Ambient conditions**
**Temperature**

Operating temperature

min	°C	-50
max	°C	+70

Storage temperature

min	°C	-60
max	°C	+80

Max altitude

m 3000

**Resistance & Protection**

Pollution degree

3