



Product designation	Power contactor		
Product type designation	BG09		
Contact characteristics			
Number of poles	Nr.	4	
Rated insulation voltage Ui IEC/EN	V	690	
Rated impulse withstand voltage $Uimp$	kV	6	
Operational frequency	min	Hz	25
	max	Hz	400
IEC Conventional free air thermal current Ith		A	20
Operational current Ie	AC-1 ($\leq 40^{\circ}\text{C}$) A 20 AC-1 ($\leq 55^{\circ}\text{C}$) A 18 AC-1 ($\leq 70^{\circ}\text{C}$) A 15 AC-3 ($\leq 440\text{V} \leq 55^{\circ}\text{C}$) A 9 AC-4 (400V) A 4		
Rated operational power AC-1 ($T \leq 40^{\circ}\text{C}$)	230V	kW	8
	400V	kW	14
	500V	kW	16
	690V	kW	22
IEC max current Ie in DC1 with $L/R \leq 1\text{ms}$ with 1 poles in series	$\leq 24\text{V}$	A	12
	48V	A	10
	75V	A	4
	110V	A	3
	220V	A	—
IEC max current Ie in DC1 with $L/R \leq 1\text{ms}$ with 2 poles in series	$\leq 24\text{V}$	A	15
	48V	A	14
	75V	A	9
	110V	A	8
	220V	A	—
IEC max current Ie in DC1 with $L/R \leq 1\text{ms}$ with 3 poles in series	$\leq 24\text{V}$	A	16
	48V	A	16
	75V	A	10
	110V	A	10
	220V	A	2
IEC max current Ie in DC1 with $L/R \leq 1\text{ms}$ with 4 poles in series	$\leq 24\text{V}$	A	16
	48V	A	16
	75V	A	10
	110V	A	10
	220V	A	2

IEC max current I_e in DC3-DC5 with $L/R \leq 15\text{ms}$ with 1 poles in series

$\leq 24\text{V}$	A	7
48V	A	6
75V	A	2
110V	A	1
220V	A	—

IEC max current I_e in DC3-DC5 with $L/R \leq 15\text{ms}$ with 2 poles in series

$\leq 24\text{V}$	A	8
48V	A	8
75V	A	5
110V	A	4
220V	A	—

IEC max current I_e in DC3-DC5 with $L/R \leq 15\text{ms}$ with 3 poles in series

$\leq 24\text{V}$	A	10
48V	A	10
75V	A	6
110V	A	5
220V	A	0,8

IEC max current I_e in DC3-DC5 with $L/R \leq 15\text{ms}$ with 4 poles in series

$\leq 24\text{V}$	A	10
48V	A	10
75V	A	6
110V	A	5
220V	A	0,8

Short-time allowable current for 10s (IEC/EN60947-1)

A 96

Protection fuse

gG (IEC)	A	20
aM (IEC)	A	10

Making capacity (RMS value)

A 92

Breaking capacity at voltage

440V	A	72
500V	A	72
690V	A	72

Resistance per pole (average value)

mΩ 10

Power dissipation per pole (average value)

I _{th}	W	4
AC-3	W	0.81

Tightening torque for terminals

min	Nm	0.8
max	Nm	1
min	I _{bin}	9
max	I _{bin}	9

Tightening torque for coil terminal

min	Nm	0.8
max	Nm	1
min	I _{bin}	9
max	I _{bin}	9

Max number of wires simultaneously connectable

Nr. 2

Conductor section

AWG/Kcmil	max	12
Flexible w/o lug conductor section	min	mm ² 0.75

	max	mm ²	2.5	
Flexible c/w lug conductor section	min	mm ²	1.5	
	max	mm ²	2.5	
Flexible with insulated spade lug conductor section	min	mm ²	1.5	
	max	mm ²	2.5	
Power terminal protection according to IEC/EN 60529			IP20 when properly wired	
Mechanical features				
Operating position	normal allowable		Vertical plan ±30°	
Fixing			Screw / DIN rail 35mm	
Weight	g		183	
Auxiliary contact characteristics				
Thermal current I _{th}	A		10	
IEC/EN 60947-5-1 designation			A600	
Operations				
Mechanical life	cycles		20000000	
Electrical life	cycles		500000	
Safety related data				
Performance level B10d according to EN/ISO 13489-1	rated load mechanical load	cycles	500000 20000000	
EMC compatibility			yes	
AC coil operating				
Rated AC voltage at 60Hz	V		460	
AC operating voltage	of 60Hz coil powered at 60Hz pick-up	min max	%Us %Us	75 115
	drop-out	min max	%Us %Us	20 55
AC average coil consumption at 20°C				
of 50/60Hz coil powered at 50Hz	in-rush holding	VA	30 4	
of 50/60Hz coil powered at 60Hz	in-rush holding	VA	25 3	
of 60Hz coil powered at 60Hz	in-rush holding	VA	30 4	
Dissipation at holding ≤20°C 50Hz		W	0.95	
Max cycles frequency				
Mechanical operation		cycles/h	3600	
Operating times				
Average time for Us control				
in AC	Closing NO			

		min	ms	12
		max	ms	21
Opening NO				
		min	ms	9
		max	ms	18
Closing NC				
		min	ms	17
		max	ms	26
Opening NC				
		min	ms	7
		max	ms	17

in DC

	Closing NO		min	ms	18
			max	ms	25
Opening NO			min	ms	2
			max	ms	3
Closing NC			min	ms	3
			max	ms	5
Opening NC			min	ms	11
			max	ms	17

UL technical data

Rated operational voltage AC (UL)	V	600
Full-load current (FLA) for three-phase AC motor		

at 480V	A	7.6
at 600V	A	6.1

Yielded mechanical performance

for single-phase AC motor	110/120V	HP	0.5
	230V	HP	1.5
for three-phase AC motor			
	200/208V	HP	2
	220/230V	HP	3
	460/480V	HP	5
	575/600V	HP	5

General USE

Contactor	AC current	A	20
-----------	------------	---	----

Short-circuit protection fuse, 600V

High fault	Short circuit current	kA	100
	Fuse rating	A	30
	Fuse class		J
Standard fault			
	Short circuit current	kA	5
	Fuse rating	A	30
	Fuse class		RK5

Ambient conditions

Temperature	Operating temperature	min	°C	-50
-------------	-----------------------	-----	----	-----

	max	°C	+70
Storage temperature	min	°C	-60
	max	°C	+80
Max altitude	m		3000
Resistance & Protection			
Pollution degree			3
ETIM classification			EC000066 - Power contactor, AC switching
ETIM 8.0			