


Product information

The ALU labelling material, in mat size 300x200 mm, has been developed especially for engraving.

- Coloured anodised aluminium material
- Available with self-adhesive foil / adhesive foil
- Individual or prefab labels
- Temperature range up to approx. 200 °C
- Thickness: 1.0 mm
- marking technique: Engraving

Material thickness mm: 1



Information, conformities and approvals



Article	Order No.	Color	Label size mm	Number x Holes mm	Quantity per mat	Software Article	PU pcs.		
Without corner radius; with adhesive foil									
ALU 30x70 HF, 4x3.0MM ¹⁾	8604246002	Black anodized	70 x 30	4x 3.0	20	1L	20		
ALU 60x20 HF, 4x3.5MM ¹⁾	8604946000	Silver anodized	60 x 20	4x 3.5	50	057	50		
ALU 60x30 HF, 4x5.0MM ¹⁾	8604246001	Silver anodized	60 x 30	4x 5.0	30	888	30		
ALU 80x50 HF, 4x3.5MM ¹⁾	8604246007	Black anodized	80 x 50	4x 3.5	12	G48	12		
ALU 85x180 HF, 4x3.4MM ¹⁾	8604246009	Silver anodized	85 x 180	4x 3.4	3	K24	3		
ALU 90x45 HF, 4x3.2MM ¹⁾	8604246003	Silver anodized	90 x 45	4x 3.2	12	30	12		
ALU 90x45 HF, 4x3.2MM ¹⁾	8604246011	Blue anodized	90 x 45	4x 3.2	12	Z84	12		
ALU 100x75 HF, 4x2.6MM ¹⁾	8604246000	Silver anodized	100 x 75	4x 2.6	6	656	6		
ALU 100x155 HF, 4x2.5MM ¹⁾	8604246004	Silver anodized	100 x 155	4x 2.5	3	5V	3		
ALU 140x100 HF, 4x2.5MM ¹⁾	8604246005	Silver anodized	140 x 100	4x 2.5	4	5W	4		






Order No.	Color	Label size mm	Number x Holes mm	Quantity per mat	Software Article	PU pcs.		
8604246006	Silver anodized	150 x 80	4x 4.0	4	8W	4		
8604246010	Black anodized	150 x 200	4x 3.5	2	L60	2		
Without corner radius; with self-adhesive foil								
8604240002	Silver anodized	100 x 70	4x 3.2	8	226	8		
8604240003	Black anodized	90 x 45	4x 3.0	12	Z63	12		
	8604246006 8604246010 self-adhesive foil 8604240002	8604246006Silver anodized8604246010Black anodizedself-adhesive foil8604240002Silver anodized	8604246006 Silver anodized 150 x 80 8604246010 Black anodized 150 x 200 self-adhesive foil	8604246006 Silver anodized 150 x 80 4x 4.0 8604246010 Black anodized 150 x 200 4x 3.5 self-adhesive foil	8604246006 Silver anodized 150 x 80 4x 4.0 4 8604246010 Black anodized 150 x 200 4x 3.5 2 self-adhesive foil	8604246006 Silver anodized 150 x 80 4x 4.0 4 8W 8604246010 Black anodized 150 x 200 4x 3.5 2 L60 self-adhesive foil 8604240002 Silver anodized 100 x 70 4x 3.2 8 226		

¹⁾ Other sizes available on request







Engraving material Dimension table

Article	Order No.	Drill hole pitch X mm	Drill hole pitch Y mm	Drill hole position X1 mm	Drill hole position Y1 mm	Drill hole position X2 m
Without corner radius; with	adhesive foil					
ALU 30x70 HF, 4x3.0MM ¹⁾	8604246002	24	64	3	3	27
ALU 60x20 HF, 4x3.5MM ¹⁾	8604946000	50	10	5	5	55
ALU 60x30 HF, 4x5.0MM ¹⁾	8604246001	50	20	5	5	55
ALU 80x50 HF, 4x3.5MM ¹⁾	8604246007	69.5	39.5	5.25	5.25	74.75
ALU 85x180 HF, 4x3.4MM ¹⁾	8604246009	60	170	12.5	5	72.5
ALU 90x45 HF, 4x3.2MM ¹⁾	8604246003	78	33	6	6	84
ALU 90x45 HF, 4x3.2MM ¹⁾	8604246011	78	33	6	6	84
ALU 100x75 HF, 4x2.6MM ¹⁾	8604246000	92	67	4	4	96
ALU 100x155 HF, 4x2.5MM ¹⁾	8604246004	88	143	6	6	94
ALU 140x100 HF, 4x2.5MM ¹⁾	8604246005	128	88	6	6	134
ALU 150x80 HF, 4x4.0MM ¹⁾	8604246006	140	70	5	5	145
ALU 150x200 HF, 4x3.5MM ¹⁾	8604246010	140	190	5	5	145
Without corner radius; with	self-adhesive foi	1				
ALU 70x100 SK, 4x3,2MM ¹⁾	8604240002	60	90	5	5	65
ALU 90x45 SK, 4x3,0MM ¹⁾	8604240003	82	37	4	4	86
¹⁾ Other sizes available on requ	unct					

¹⁾ Other sizes available on request





Material properties



Aluminium anodised (ALU)

Thermal properties



Temperature / temperature range -40 °C – 140 °C

General technical data



Single-line and multi-line labelling

Labelling technology



Engraving

Adhesive properties



467 SK adhesive film with adhesive

Fire properties



Fire classification V0

Assembly method



Screw system

All details given in our sales brochures and catalogues, as well as the information available online, are based on our current knowledge of the products described. The electronic data and files made available by Murrplastik, particularly CAD files are based on our current knowledge of the products described. A legally binding assurance of certain properties or the suitability for a certain purpose can not be determined from this information. All information with respect to the chemical and physical properties of Murrplastik products, as well as application advice given verbally, in writing or by tests, is given to the best of our knowledge. They do not release the buyer from the obligation to carry out his own tests and trials in order to determine the concrete suitability of the products for the intended purpose. Murrplastik accepts no sponsibility for the available information heing up-to-date, correct or complete. Neither do we accept responsibility of the quality of this information. Murrplastik accepts no liability for damage caused as a result of using our products. Murrplastik reserves the right to make technical changes and improvements through constant further development of products and services. Our General Terms and Conditions apply.