





LA Rectangular without radius, 4x oblong hole







Product information

The laser has served us well for years, especially for engraving and labeling of metals.

Laser Aluminum (LA) can be marked with high contrast, durable, precise, legible and fast with Murrplastik laser systems.

Custom configuration Various colours Different geometries and holes Three different carrier materials available

A suction and filter unit is absolutely necessary to comply with legal regulations on health protection.

Information, conformities and approvals





| Article | Order No. | Color | Material thick- ness mm | Printable area mm | No. characters/ lines | Hole pat- terns Num- ber x Ø mm | No. per Frame | Software Article | PU pcs. |
|----------------------------|------------|--------|----------------------------------|-------------------|-----------------------|--|------------------|------------------|---------|
| Rectangular desi | | | | | | | | | |
| LA 60x12 HF, 4x (4x2MM) | 8610100268 | Silver | 1 | 42 x 12 | 23 / 3 | 4 _X | 8 | NG4 | 32 |

Laser labelling material dimensions table

| Article | Order No. | Drill hole pitch X mm | Drill hole pitch Y mm | Drill hole position X1 mm | Drill hole position Y1 mm | Drill hole position X2 mm | Drill hole position Y2 mm | |
|---------------------------------|-----------------|-----------------------------|--------------------------|------------------------------|------------------------------|------------------------------|------------------------------|--|
| Rectangular desid | nn with & clote | | | | | | | |
| nectangular uesign with 4 sicio | | | | | | | | |
| LA 60x12 HF, 4x (4x2MM) | 8610100268 | 50 | 6 | 5 | 3 | 55 | 9 | |

© Murrplastik Systemtechnik GmbH • 1 as of 2024-11-12 - 187632





LA Rectangular without radius, 4x oblong hole

Material properties



Aluminium anodised (ALU)

Adhesive properties



467, 5016 SK adhesive film with adhesive, SKS adhesive film with foam adhesive

Thermal properties



Temperature / temperature range -40 $^{\circ}$ C – 140 $^{\circ}$ C short termshort term: 200 $^{\circ}$ C

Fire properties



Fire classification V0

General technical data

° Standard product, available from stock

Industry standard color deviations possible

Assembly method



Cable ties

Labelling technology



Lasei

All details given in our sales brochures and catalogues, as well as the information available online, are based on our current knowledge of the products described. The electronic data and files made available by Murrplastik, particularly CAD files are based on our current knowledge of the product described. A legally binding assurance of certain properties or the suitability for a certain purpose can not be determined from this information. All information with respect to the chemical and physical properties of Murrplastik products, as well as application advice given verbally, in writing or by tests, is given to the best of our knowledge. They do not release the buyer from the obligation to carry out his own tests and trials in order to determine the concrete suitability of the products for the intended purpose. Murrplastik accepts no responsibility for the available information being up-to-date, correct or complete. Neither do we accept responsibility for the quality of this information. Murrplastik accepts no liability for damage caused as a result of using our products. Murrplastik reserves the right to make technical changes and improvements through constant further development of products and services. Our General Terms and Conditions apply.