

|                                                        |                                      |    |           |
|--------------------------------------------------------|--------------------------------------|----|-----------|
| Product designation                                    | Rotary cam switches                  |    |           |
| Product type designation                               | GX32                                 |    |           |
| General characteristics                                |                                      |    |           |
| Switching diagram                                      | 06 - ON/OFF switch 2 poles           |    |           |
| N° of elements                                         | 1                                    |    |           |
| Mounting form                                          | U - Front mounting with black handle |    |           |
| Contact characteristics                                |                                      |    |           |
| Rated insulation voltage Ui                            | IEC/EN                               | V  | 690       |
|                                                        | UL/CSA                               | V  | 600       |
| Rated impulse withstand voltage Uimp                   |                                      | kV | 6         |
| Conventional free air thermal current Ith              | IEC/EN                               | A  | 32        |
|                                                        | UL/CSA                               | A  | 32        |
| Rated operational voltage                              |                                      | V  | 440       |
| Rated operational impulse voltage                      |                                      | kV | 4         |
| Maximum fuse size for short-circuit protection In (gG) | 10kA                                 | A  | 35        |
|                                                        | 15kA                                 | A  | 35        |
|                                                        | 25kA                                 | A  | 35        |
| Rated short time current Icw                           | 1s                                   | kA | 1000      |
| Conductivity                                           |                                      |    | 10/5 mA/V |
| Operational current Ie IEC/EN                          |                                      |    |           |
| AC1/AC21A                                              |                                      | A  | 32        |
| AC15                                                   | 110V                                 | A  | 25        |
|                                                        | 220/230V                             | A  | 20        |
|                                                        | 380/400V                             | A  | 10        |
|                                                        | 660/690V                             | A  | 2         |
| Rated operational power in AC                          |                                      |    |           |
| Three-phase AC-3                                       | 220/230V                             | kW | 7.5       |
|                                                        | 380/440V                             | kW | 11        |
|                                                        | 500/690V                             | kW | 11        |
| Single-phase AC-3                                      | 110V                                 | kW | 1.8       |
|                                                        | 220/230V                             | kW | 3.5       |
|                                                        | 380/440V                             | kW | 5.5       |
| Three-phase AC23A                                      | 220/230V                             | kW | 8         |
|                                                        | 380/440V                             | kW | 15        |
|                                                        | 500/690V                             | kW | 15        |
| Single-phase AC23A                                     | 110V                                 | kW | 2.2       |
|                                                        | 220/230V                             | kW | 3.5       |
|                                                        | 380/440V                             | kW | 6         |
| Rated operational current in DC                        |                                      |    |           |

### DC21A

|      |   |      |
|------|---|------|
| 48V  | A | 32   |
| 60V  | A | 32   |
| 110V | A | 5    |
| 220V | A | 0.8  |
| 440V | A | 0.25 |

### DC23A (poles in series)

|      |   |        |
|------|---|--------|
| 24V  | A | 32 (1) |
| 48V  | A | 32 (2) |
| 60V  | A | 32 (3) |
| 110V | A | 15 (3) |
| 220V | A | 12 (4) |

### DC13

|      |   |      |
|------|---|------|
| 24V  | A | 32   |
| 48V  | A | 25   |
| 60V  | A | 14   |
| 110V | A | 3    |
| 220V | A | 0.5  |
| 440V | A | 0.15 |

|                   |   |     |
|-------------------|---|-----|
| Power dissipation | W | 1.6 |
|-------------------|---|-----|

### Mechanical features

|                 |    |
|-----------------|----|
| Terminals screw | M4 |
|-----------------|----|

|                                     |    |     |
|-------------------------------------|----|-----|
| Tightening torque for terminals max | Nm | 1.2 |
|-------------------------------------|----|-----|

### Conductor size

#### AWG - Rigid cable

|     |     |    |
|-----|-----|----|
| min | AWG | 16 |
| Max | AWG | 8  |

#### AWG - Flexible cable

|     |     |    |
|-----|-----|----|
| min | AWG | 16 |
| Max | AWG | 10 |

#### Conductor size (IEC) - Flexible cable

|     |                 |     |
|-----|-----------------|-----|
| min | mm <sup>2</sup> | 1.5 |
| Max | mm <sup>2</sup> | 6   |

#### Conductor size (IEC) - Rigid cable

|     |                 |     |
|-----|-----------------|-----|
| min | mm <sup>2</sup> | 1.5 |
| Max | mm <sup>2</sup> | 10  |

|                 |        |                   |
|-----------------|--------|-------------------|
| Mechanical life | cycles | 1X10 <sup>6</sup> |
|-----------------|--------|-------------------|

### UL technical data

#### Motor power for direct-on-line control

##### for three-phase motor

|      |    |     |
|------|----|-----|
| 120V | HP | 3   |
| 240V | HP | 7.5 |
| 480V | HP | 15  |
| 600V | HP | 15  |

##### for single-phase motor

|      |    |     |
|------|----|-----|
| 120V | HP | 1.5 |
| 240V | HP | 3   |

### Ambient conditions

#### Temperature

##### Operating temperature

|     |    |     |
|-----|----|-----|
| min | °C | -25 |
| max | °C | +55 |

##### Storage temperature

|     |    |     |
|-----|----|-----|
| min | °C | -40 |
|-----|----|-----|

max °C +70

## Resistance & Protection

Frontal IP degree IP65


Terminals IP degree IP20

## Dimensions



| Series | Dimensions |      |     |     |      |    |   | L Number of elements |      |    |      |    |      |     |       |     |       |     |       |
|--------|------------|------|-----|-----|------|----|---|----------------------|------|----|------|----|------|-----|-------|-----|-------|-----|-------|
|        | A          | C    | ØD1 | ØD2 | E    | K  | N | 1                    | 2    | 3  | 4    | 5  | 6    | 7   | 8     | 9   | 10    | 11  | 12    |
| GX16   | 48         | 39.5 | 12  | 5   | 26.5 | 36 | 6 | 43                   | 51.5 | 60 | 68.5 | 77 | 85.5 | 94  | 102.5 | 111 | 119.5 | 128 | 136.5 |
| GX20   | 48         | 39.5 | 12  | 5   | 26.5 | 36 | 6 | 43                   | 51.5 | 60 | 68.5 | 77 | 85.5 | 94  | 102.5 | 111 | 119.5 | 128 | 136.5 |
| GX32   | 65         | 53   | 14  | 5   | 34.5 | 48 | 7 | 51                   | 63   | 75 | 85   | 99 | 111  | 123 | 135   | 147 | 159   | 171 | 183   |
| GX40   | 65         | 53   | 14  | 5   | 34.5 | 48 | 7 | 51                   | 63   | 75 | 85   | 99 | 111  | 123 | 135   | 147 | 159   | 171 | 183   |

## Wiring diagrams



## Certifications and compliance

### Compliance

CSA C22.2 n° 14

IEC/EN/BS 60947-1

IEC/EN/BS 60947-3

IEC/EN/BS 60947-5-1

IEC/EN/BS 61058-1

UL60947-4-1

### Certificates

cULus

EAC

## ETIM classification

ETIM 8.0

EC001029 -  
Selector switch,  
complete