



Type ELD/K



Product information

The ELD/K conduit fitting is made of specially modified polypropylene. The fitting is equipped with a rotatable connection thread into which the conduit is screwed. The upper part of the fitting is also rotatable. The ELD/K fitting is characterised by its guick and easy assembly without the use of

The ELD/K fitting is characterised by its quick and easy assembly without the use of any special tools and can be used for EL, ELS and EVK cable protection conduits.

Information, conformities and approvals





Article	Order No.	Color	Connecting thread	Suitable for EL	Suitable for ELS	Suitable for EVK	GL mm	EH mm	SW mm	PU pcs.
ELD/K M20x1.5 1)	83741416	Gray	M20x1,5	11	11	09/E	10	30	22	50
ELD/K M25x1.5 1)	83741418	Gray	M25x1,5	16	16	11	11	34	27	50
ELD/K M32x1.5	83741420	Gray	M32x1,5	21	21	21/E	12	42.7	35	25
ELD/K M40x1.5 1)	83741422	Gray	M40x1,5	29	29	29/E	12	44	45	25
ELD/K M50x1.5 1)	83741424	Gray	M50x1,5	36	36	36/E	12	47.5	54	25
ELD/K M63X1.5 1)	83741426	Gray	M63x1,5	48	48	42	15	50	65	10
ELD/K PG 07 2) 1)	83741210	Gray	PG 07	07	07	11	10	23	16	50
ELD/K PG 09 2)	83741212	Gray	PG 09	09	09	07/E	10	27.5	19	50
ELD/K PG 11 2)	83741214	Gray	PG 11	11	11	09/E	10	30	22	50
ELD/K PG 13 2) 1)	83741215	Gray	PG 13	13	13	11/E	10	30	24	50
ELD/K PG 16 2)	83741216	Gray	PG 16	16	16	11	11	34	27	50
ELD/K PG 21 2)	83741220	Gray	PG 21	21	21	21/E	11	44	35	25
ELD/K PG 29 1) 1)	83741224	Gray	PG 29	29	29	29/E	12	44	45	25





Type ELD/K

Article	Order No.	Color	Connecting thread	Suitable for EL	Suitable for ELS	Suitable for EVK	GL mm	EH mm	SW mm	PU pcs.
ELD/K PG 36 2)	83741226	Gray	PG 36	36	36	36/E	12	47.5	54	25
ELD/K PG 42 2)	83741227	Gray	PG 42	42	42	36/E	12	49.5	61	10
ELD/K PG 48 2)	83741228	Gray	PG 48	48	48	42	15	50	65	10
1) No stock goods, de 2) Discontinued prod	elivery time and minimu luct!	m order quantities u	pon request							
1) No stock goods, delivery time and minimum order quantities upon request										

Material properties



Polypropylene (PP) |

Thermal properties



-10 °C - 110 °C

Protection class



Fire properties

acc. to UL94: HB



All details given in our sales brochures and catalogues, as well as the information available online, are based on our current knowledge of the products described. The electronic data and files made available by Murrplastik, particularly CAD files are based on our current knowledge of the products described. A legally binding assurance of certain properties or the suitability for a certain purpose can not be determined from this information. All information with respect to the chemical and physical properties of Murrplastik products, as well as application advice given verbally, in writing or by tests, is given to the best of our knowledge. They do not release the buyer from the obligation to carry out his own tests and trials in order to determine the concrete suitability of the products for the intended purpose. Murrplastik accepts no responsibility for the available information being up-to-date, correct or complete. Neither do we accept responsibility of the quality of this information. Murrplastik accepts no liability for damage caused as a result of using our products. Murrplastik reserves the right to make technical changes and improvements through constant further development of products and services. Our General Terms and Conditions apply.